

Reg No.: _____

Name: _____

APJ ABDUL KALAM TECHNOLOGICAL UNIVERSITY
SEVENTH SEMESTER B.TECH DEGREE EXAMINATION(S), MAY 2019

Course Code: EE409

Course Name: Electrical Machine Design

Max. Marks: 100

Duration: 3 Hours

PART A

Answer all questions, each carries 5 marks.

Marks

- | | | |
|---|---|-----|
| 1 | What is meant by hot spot rating in electrical machines? | (5) |
| 2 | Compare the reluctance of slotted armature with that of smooth armature surface. | (5) |
| 3 | Derive the output equation of DC machine. | (5) |
| 4 | Explain different types of cooling systems used in synchronous machines. | (5) |
| 5 | List out and explain the factors to be considered for selection of specific electric loading in 3-phase induction motors. | (5) |
| 6 | State the main constructional differences between cage induction motor and slip ring induction motor. | (5) |
| 7 | Explain synthesis method for computer aided design of electrical machines | (5) |
| 8 | Explain on few softwares used for designing electrical machines? | (5) |

PART B

Answer any two full questions, each carries 10 marks.

- | | | |
|----|---|-----|
| 9 | a) Examine any four components of armature leakage flux. | (4) |
| | b) Derive the relation between real and apparent flux densities. | (6) |
| 10 | a) Derive the output equation for 3 phase core type transformer. | (4) |
| | b) Determine the dimensions of core and yoke for a 200KVA 50Hz single phase core type transformer. A cruciform core is used with distance between adjacent limbs equal to 1.6 times width of core laminations. Assume voltage per turn 14 V, maximum flux density 1.1 Wb/m^2 , window space factor 0.32, current density 3 A/mm^2 and stacking factor 0.9. The net iron area is $0.56d^2$ in a cruciform core where d is the diameter of circumscribing circle and width of largest stamping is $0.85d$. | (6) |
| 11 | a) Explain unbalanced magnetic pull in rotating electrical machines. | (5) |
| | b) Derive the ratio of gross core area to area of circumscribing circle for a square core of a transformer. | (5) |

PART C

Answer any two full questions, each carries 10 marks.

- 12 a) Explain the flux pulsation produced in dc machine. (5)
b) Explain step by step design procedure of brushes and commutator in a DC machine. (5)
- 13 Find the main dimensions of a 100 MVA, 11kV, 50 Hz, 150 rpm, 3 phase water wheel generator. The average gap density is 0.65 Wb/m^2 and the ampere conductors per meter is 40000. The peripheral speed should not exceed 65m/s at normal running speed in order to limit the run away peripheral speed. Assume the winding factor to be 0.955. (10)
- 14 a) Explain step by step design procedure for armature of a dc machine. (5)
b) Find the main dimensions of a 2500 kVA, 187.5 rpm, 50 Hz, 3 phase, 3 kV, salient pole synchronous generator. The generator is to be vertical, water wheel type. The specific electric loading is 34000 A/m and B_{av} is 0.6 Wb/m^2 . Use circular poles with ratio of core length to pole pitch to be 0.65. Specify the type of pole construction used if the run-away speed is about 2 times the normal speed. (5)

PART D

Answer any two full questions, each carries 10 marks.

- 15 a) How do the iron losses affect selection of B_{av} ? (5)
b) Explain cogging and crawling in 3-phase induction machines. (5)
- 16 a) Explain on Analysis method of solving electrical machine using CAD with a flow chart. (6)
b) What are the advantages of analysis method? (4)
- 17 a) Design the main dimensions of a 25 kW, 3 phase, 415V, 50 Hz, 1475 rpm squirrel cage induction motor having an efficiency of 85 % and full load power factor of 0.86. Assume $B_{av} = 0.5T$, $a_c = 28000A/m$. The rotor peripheral velocity is 25 m/s at synchronous speed. (5)
b) Explain the steps involved in the computer aided design and analysis of electrical machines. (5)
